

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20150622-E312057  
**Report Reference** E312057-20140718  
**Issue Date** 2015-JUNE-22

**Issued to:** DEWIT INDUSTRIAL SENSORS BV  
Oostergracht 40  
3763 LZ Soest NETHERLANDS

**This is to certify that representative samples of** PROXIMITY SWITCHES  
SEE ADDENDUM PAGE


Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** UL 60947-5-2. Low-Voltage Switchgear and Controlgear – Part 5-2: Control Circuit Devices and Switching Elements – Proximity Switches  
CSA C22.2 No. 14-13, Industrial Control Equipment

**Additional Information:** See the UL Online Certifications Directory at [www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20150622-E312057  
**Report Reference** E312057-20140718  
**Issue Date** 2015-JUNE-22

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Class 2, Proximity switches, Inclination sensors, Series QG, followed by 30, 40, 65 or 76, may be followed by N,P,B,X or empty space, followed by K,M,C or S, followed by I, D or A, followed by X,Y,Z,O or empty space, followed by h, v, hv or empty space, followed by any number between 0,1G - 16G or by any number between 001-360, followed by E, F, H, X, S or empty space, followed by 2 or empty space, followed by AV, AV2, AV3, AV4, AV5, AI, IO, ASN, ASP, ASC, SPI, CAN, CANJ, CANS, PWM, or 232, may be followed by empty space, followed by C, M or F, followed by 5V or empty space, followed by UL, may be followed by any combination of characters.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

